

FT6031 Earth Testing



IP67 waterproof and dustproof -
1st in the industry!



- 0 to 2000Ω measurement range
- Innovative earthing rods and cable winder
- Switchable between two- and three-electrode methods



Innovative sliding cover system lets you store test leads while connected

3490 Multi-range Analog



- ✓ Precise taut-band movement gives quick readings
- ✓ Constant battery check
- ✓ Luminous scale
- ✓ Optional lighted remote control test lead makes testing even faster
- ✓ Check for live circuits
- ✓ Bright red light warns of live voltage

IR4056/IR4057 1kV Digital



- ✓ Check for live circuits
 - ✓ Digital reading at a glance
 - ✓ Bright red light warns of live voltage
- IR4057-20:**
- ✓ 0.3s comparator response rate
 - ✓ Digital bar graph



Safety shutter
prevents
high voltage
contact

3455 5kV Insulation Tester

Step voltage
testing, temperature
compensation,
temperature
measurement, and
leakage current



		Analog	Digital		
		3490	3455	IR4056-20	IR4057-20
Insulation Testing	50V			100 MΩ	100 MΩ
	125V			250 MΩ	250 MΩ
	250V	100 MΩ	250GΩ	500MΩ	500MΩ
	500V	100 MΩ	500GΩ	2000MΩ	2000MΩ
	1000V	4 GΩ	1.00TΩ	4000MΩ	4000MΩ
	2500V		2.50TΩ		
	5000V		5.00TΩ		
Rated Current/Short Circuit Current	1mA (Tolerance: 1 to 1.2 times of the rating value)		2mA	1.2mA	
AC V Testing	0 to 600 V (50/60 Hz)		50 to 750V	420V/600V	
DCV Testing			±50V to 1.00kV	4.2V to 600V	
Best Accuracy	±5% of maximum scale value		±5% rdg. ±5dgt.	±2.3% rdg. ±8 dgt. (ACV)	