

FT6380 Series

Clamp On Earth Tester

CATIV
600V Safe,
Accuracy and
Repeatability

Zero
adjustment not
required



Slim jaw for
the narrowest
spaces also
minimizes dirt



Bluetooth®
connectivity
for wireless
data transfer
to Android™
phones (FT6381)

- ▶ For multiple grounded systems
- ▶ 0.20Ω to 1600Ω, ±1.5% rdg. best accuracy
- ▶ 20mA to 60A current testing
- ▶ Measurements update every 1/2 second
- ▶ IP40 dust and moisture protection
- ▶ 35 hours of continuous use

3554

Battery HiTESTER

Wide 60V range



Comparator function,
auto data hold and
auto data storage

Extra-strong
test probes

- ▶ Ideal for testing UPS batteries
- ▶ 3mΩ to 3Ω over 4 resistance ranges
- ▶ 1 μΩ best resolution
- ▶ 6 or 60 DC V voltage testing with 1mV resolution
- ▶ -10 to 60°C temperature testing with 0.1°C resolution
- ▶ 1 time/sec sampling
- ▶ Store 200 sets of comparator values
- ▶ Download test results and upload comparator tables via USB interface and free software
- ▶ **Also available:** Model 3555 for compact batteries covering 300mΩ to 30Ω and 3 or 30 DCV testing

3246-60

Pencil HiTESTER

600V circuit
protection
- no fuse required



Ultra-bright diode
light lets you find
hard-to-reach spots
in dark locations

Test probe fits
neatly in the back

- ▶ 4.2V to 600V AC
- ▶ 420mV to 600V DC
- ▶ Resistance
- ▶ 150 hours of continuous use on a single battery

PD3259

Digital Phase Detector



Check phase
rotation and
measure voltage
with a single unit



Large display
and IP54

Non-metallic
contact voltage
clips

- ▶ Measure 3-phase AC V and frequency
- ▶ Phase detection, open phase and prediction of ground phase, three phase 90.0 to 520.0 V AC
- ▶ Use on covered cables and metal terminals